

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Arno Kleinhaeni et al.	:	
	:	
Serial No. 10/018,060	:	
	:	
Confirmation No. 1183	:	Group Art Unit:
	:	
Filing Date: 10-DEC-01	:	Examiner:
	:	
For: SECURITY REVERSIBLE KEY	:	
AND LOCKING SYSTEM	:	
	:	
Attorney Docket: FRR-12782	:	

Assistant Commissioner for Patents
Washington, D.C. 20231

SUPPLEMENTAL PETITION AND STATEMENT
(UNDER 37 CFR §1.47)

Sir:

1. This Petition and Statement Under 37 CFR §1.47 is being submitted because one of the two joint inventors, namely Roman Mathiuet, cannot be found or reached after diligent effort and is thus unavailable to sign the Declaration under 37 CFR §1.63.

2. The undersigned is patent counsel for the inventors in Switzerland and with respect to certain related International applications. The undersigned furthermore has first hand knowledge of the facts contained herein.

3. The last known address for the nonsigning inventor, Roman Mathiuet, is Kiesweid 17, 8340 Hadlikon, Switzerland.

4. In addition to the efforts undertaken previously and set forth in the undersigned's petition dated June 24, 2002 and submitted to the Patent Office in June 25, 2002, the following efforts have been undertaken in an effort to locate Roman Mathiuet:

- On August 20, 2002 a registered letter including Declaration, a copy of the actual version of the US Patent Application (U.S. Serial No. 10/018,060 filed December 10, 2001) was sent to the last known address of Roman Mathiuet. This letter came back unanswered on August 22, 2002. The letter, an English translation of the letter, and the envelope is enclosed.
- Several telephone books of Switzerland were considered once again, especially the official telephone book of Switzerland. There is still no entry under the name of Roman Mathiuet. Two copies of telephone book extracts showing this result are enclosed.
- On June 20, 2002 a fax was sent to the registration office of the local administration of Hinwil, Switzerland, where Roman Mathiuet was last registered. In certain cases they have new contact addresses. A copy of this

fax is also enclosed. According to the registration office Roman Mathiuet left Switzerland, possibly for Portugal.

- Two online telephone books of Portugal were considered. There is no entry under the name of Roman Mathiuet. Two copies of telephone book extracts showing this result are enclosed.
- All telephone book entries for the name 'Mathiuet' in Switzerland were used to contact persons named Mathiuet to find any relatives of Roman Mathiuet. We identified, and telephonically contacted Mr. Mathiuet's brother, Daniel Mathiuet, and his father, Karl Mathiuet. Karl Mathiuet was unwilling to give the undersigned Roman Mathiuet's current address, telephone number, or contact information. Karl Mathiuet also refused to pass along any information from the undersigned to Roman Mathiuet. Daniel Mathiuet said he did not have any contact information or telephone number for Roman Mathiuet, but he did provide the undersigned with an e-mail address that he believed might possibly be used by Roman Mathiuet. The undersigned attempted to send an e-mail message to Roman Mathiuet, but the message was returned immediately because the address was incorrect. On August 27, 2002 we further attempted to send an e-mail message to Roman Mathiuet using a slightly modified e-mail address (.com instead of .ch). To date, no response to that e-mail, a copy of which is attached, has been received by the undersigned.

5. We have used all reasonable means within our knowledge to contact and locate Roman Mathiuet. These attempts have been exhaustive, and have caused significant expenditures of time and money. Despite these efforts, Roman Mathiuet has not been found or contacted, and remains completely unavailable.

6. I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.



Willi Lanker

Date: September 5, 2002

ATTACHMENTS TO SUPPLEMENTAL PETITION
AND STATEMENT (UNDER 37 CFR §1.47)

In re Arno Kleinhaeni et al.
Serial No. 10/018,060
Filed December 10, 2001
Confirmation No. 1183

REGISTERED

Mr.
Roman Mathiuet
Kiesweid 17
8340 Hadlikon

August 20, 2002/yk

U.S. Patent Application No. 10/018,060
"Security reversible key and locking system"

Your Ref.: ---

Our Ref.: P1651 US

Dear Mr. Mathiuet

Enclosed please find the following documents:

- ☐ Declaration
- ☐ A Copy of the Actual Version of the Application
- ☐ Assignment

Please return the dated and signed Declaration as soon as possible. Please note that the Declaration has to be filed with the USPTO until **September 14, 2002.**

With kind regards
FREI PATENTANWALTSBÜRO

Albert Meier

DECLARATION

In the matter of U.S. Patent Application No. 10/018,060 in the name of KABA SCHLIESSSYSTEME AG.

I, Yvette Kuster, residing at Rütchistrasse 16, CH-8037 Zurich, Switzerland, do hereby declare that I am conversant with the English and German languages and am a competent translator thereof. I declare further that the following is a true and correct translation made by me into English of the German document attached hereto and related to U.S. Patent Application No. 10/018,060.

Signed this 20 August 2002



Yvette Kuster



serviço de informações nacionais





telephone number information > white pages directory


Information on the client


name	<input type="text" value="mathieu roman"/>		
street	<input type="text"/>	door	<input type="text"/>
city	<input type="text"/>	zip code	<input type="text"/>
search zone	<input type="text" value="National"/>	<input type="button" value="search"/>	

t
p . 8 1 1 . w w w











serviço de informações nacionais



telephone number information > white pages > search result

Sorry but no records where found for your query.

If you have any doubts or problems in making queries, please see our help pages.

New Search

t
p . 8 1 1 . w w w

[Acesso Internet](#) [Correio](#) [Chat](#) [Páginas Web](#) [Postais](#) [Compras](#) [Bilhetes](#) [Classificados](#) [Cartão Valor](#) [Telelista](#) [Tem](#)



Internet



Listas



707 222 707



Artigos
Esotéricos



Nova Pesquisa

Anuncie na Telelista

Adicionar / Alterar Registo

Contactos

Quem Somos

Telelista WAP

Admissão de Vendedores

Sugestões

Resultado da Pesquisa: Mathiuet

Não foi encontrado nenhum registo com os parâmetros de sua pesquisa. Tente novamente.

Pesquisa

***Nome da Empresa**

Ex: Telelista

Mathiuet

***Título/Actividade**

Ex: Restaurante

[Ver lista]

Distrito

-----Distrito-----

***Nº de Telefone**

Ex: 213952205

Código Postal

Ex: 1200

Concelho

-----Concelho-----

***Morada**

Ex: Infante Santo

Ordenar por:☒ Nome ☐ Cód. Postal

Pesquisar

Limpar

* Preencha pelo menos um dos campos assinalados.

Pesquisa

Pesquisa por Actividade



Camiões e Pesos Pesados, Equipamentos e Acessórios, Motorizadas e Bicicleta Automóvel, Stands, Reparações e Manutenção.



Beleza, Tratamentos e Naturais, Moda.



Animais, Artigos para Decoração e para o Lar, Construção e Materiais para o L Electrodomésticos e Equipamentos para o Lar, Jardim, Serviços úteis.



Diversos, Escolas, Orfanatos, Infantários, Parques, Médicos.



Desporto - Artigos e Prática, Hobbies, Instrumentos Musicais.



Estacionário, Consumíveis de Escritório, Brindes, Outros, Formação e Gestão d Informática, Instalações e Equipamentos, Outros Serviços, Publicidade e Mark Serviços Financeiros.



Escolas, Cursos, Academias, Universidades.

To: Roman_Mathiu@hotmail.com
From: Office-Mail <office-mail@frei-patent.com>
Subject: DRINGEND P1651 US
Cc:
Bcc:
Attached:

Sehr geehrter Herr Mathiu

Nach einer mehr oder weniger erfolglosen Suche nach Ihrem jetzigen Aufenthaltsort konnten wir Ihren Bruder ausfindig machen, der uns freundlicherweise Ihre email Adresse zur Verfügung gestellt hat.

Wir versuchen Sie schon seit längerem in einer mittlerweile dringenden Sache zu kontaktieren.

Es handelt sich um die Patentanmeldung Nr10/018,060 in der USA:
"Sicherheitswendschlüssel und Schliessystem", für welche Sie und Herrn Arno Kleinhaeni Erfinder sind.

Bei Patentanmeldungen in den USA ist es notwendig, dass die Erfinder eine Erklärung abgeben, in welcher diese bestätigen, dass sie die Erfinder sind. Es ist nicht möglich, dass ein Vertreter, auch kein bevollmächtigter, anstelle der Erfinder unterschreibt.

Eine solche Erklärung (Declaration) muss bis zum 14. September 2002 beim US Patentamt hinterlegt werden.

Wir bitten Sie deshalb sich **umgehend** bei uns zu melden und uns eine Postadresse oder vorzugsweise eine Faxnummer zukommen zu lassen, an welche wir die Deklaration zur Unterschrift schicken können.

Mit herzlichem Dank zum voraus und

Mit freundlichen Grüßen

FREI PATENTANWALTSBUERO
Dr. Yvette Kuster

Frei Patent Attorneys
Postfach 768, CH-8029 Zurich, Switzerland
Tel. +41-1-396 20 60, Fax +41-1-396 20 70
<<http://www.frei-patent.com>>
office-mail@frei-patent.com

Frei Patentanwaltsbüro

European Patent Attorneys
Conseils en Brevets Européens

Tel. 01/396 20 60
Fax 01/396 20 70

Mailing address
Postfach 768
CH-8029 Zürich

Visiting address
Orchstrasse 420
H-8702 Zollikon
(Zürich)

PER FAX

**Gemeindeverwaltung
z.Hd. Frau Brändli
Einwohnerkontrolle
8340 Hinwil**

20. Juni 2002 /ZG

Sehr geehrte Frau Brändli


Wir wären Ihnen sehr verbunden, wenn Sie uns bitte eine Kontakt-Adresse von

Herrn Roman Mathiuet mitteilen könnten.

Herr Mathiuet war bis vor ca. einem Jahr bei der Firma KABA in Wetzikon beschäftigt, und an der
Kiesweid 17, Hadlikon wohnhaft.

Im voraus besten Dank

Mit freundlichen Grüssen
FREI PATENTANWALTSBÜRO


Dr. Albert Meier

Internet webserver
<http://www.frei-patent.com>
office-mail
@frei-patent.com

Winterthur office
Jbergstrasse 64
8405 Winterthur
t. 052/232 43 66
x 052/232 33 95

Postal check
PC 80-12725-3

Bank account
S.BG/UBS Zürich
Bahnhofstrasse
Kto. 338214.01U

Member of the International Federation of Industrial Property Attorneys



[illegible]

**NEU: AutoFlight-3D -
Flug entlang der Reiseroute in 3D**

© Stufiz.com Directories AG

NC

<http://www.weisseseiten.ch/>

20.08.2002

http://www.weisseiten.ch/application/visualization/start_result-tr.asp

20.08.2002

HOMIE INFO KONTAKT FAQ GELBE SEITEN E-MAIL ADRESSEN

DIE WEISSEN SEITEN®

Ihre Werbung

Ihr Adressbook

Neue Suche

Zum Adressbuch hinzufügen Darstellung der Adressen

Go!

Keine Einträge gefunden!

wc entries found

Suche...

Meine Telefonnummer ist
(Vorwahlnummer)

Meine Mobile Nr. ist
(Vorwahlnummer)*

*Eintrag nur möglich, wenn ein Mobile-Abonnement gelöst wurde

Werbespernung für Rufnummern ☐

Werbespernung für E-Mail-Adresse ☐

E-Mail Eintrag nur im Online-Verzeichnis (Gratis) ☐

Directories erschwert den Missbrauch von persönlichen Daten (mehr zu diesem Thema finden Sie auf [Directories Ihre Privatsphäre schützt?](#)). Haben wir Sie überzeugt? Möchten Sie auch Ihre Mobile Nr. und Adresse bekanntmachen (siehe Preise)?

(c) **Societatea Comercială Pireclonia - AG**



<http://www.weissseiten.ch/>

20.08.2002

http://www.weisseiten.ch/application/visualization/start_result-tr.asp

20.08.2002

[tel.search.ch]

das elektronische Telefonbuch

[Home](#)
[Telefonbuch](#)
[Suchresultat](#)


[français](#)

sFr. 500.- Abgebühren im
 Monat...

... das muss nicht sein!

Testen Sie jetzt Ihr Mobile-Abo.

Mein Mobile-Anbieter

Bitte wählen 

Rechnungsbetrag:

CHF/Mt.

weiter

Handys & mehr...
 Riesenauswahl!

Hier klicken!

eBay.ch

Telefonbucheinträge zu Mathiuet Roman

Keine Einträge gefunden

← no entries found

Tips:

- Überprüfen Sie die Schreibweise
- Kürzen Sie die Namen und Bezeichnungen (z.B. Strassenverkehr statt Strassenverkehrsamt)
- Lassen Sie einige Felder oder Wörter weg (Es müssen *alle* ausgefüllten zutreffen!)

Eintrag suchen

Name, Vorname Branche, Beruf Strasse Ort

Kanton

Alle 

← all Switzerland

Telefon Nr.

Inklusive Vorwahl (z.B. 01 oder 01 555 1234)

Eintrag suchen

Eingaben löschen

Internationale
 Suche:

Deutschland, Frankreich, Italien, Österreich, England,
Luxemburg, USA

Web-Suche nach Stichwort:

Suchen

Suchdienste: Karte Aktuell: News, Wetter, KinoAnzeigen: Immobilien, Stellen, Fahrzeuge, Seminare,
KontakteNützlich: Last Minute, Hotels, Preisvergleiche, Gratis SMS,
Ratgeber, Grusskarten

[\[Feedback\]](#) [\[Privatsphäre\]](#) [\[Über Inhalte\]](#) [\[Nutzungsbedingungen\]](#) [\[AGB\]](#) [\[Werbung\]](#)

(C) by Räber Information Management GmbH, Search & Portal Technology (C) by IOGRAM AG.

Frei Patentanwaltsbüro

European Patent Attorneys
Conseils en Brevets Européens

Tel. 01/396 20 60
Fax 01/396 20 70

EINSCHREIBEN

Mailing address
Postfach 768
CH-8029 Zürich

Herrn
Roman Mathiuet
Kiesweid 17
8340 Hadlikon

Visiting address
Forchstrasse 420
CH-8702 Zollikon
(Zürich)

24. April 2002/RM

US-Patentanmeldung Nr. 10/018,060

"Security reversible key and locking system"

Ihr Zeichen: ---

Unser Zeichen: P1651 US

Sehr geehrter Herr Mathiuet

Als Anlage erhalten Sie folgendes Dokument:

- ☒ Deklaration
- ☐ Erfindernennung
- ☐ Übertragung

Bitte senden Sie uns dieses Dokument datiert und signiert in den nächsten Tagen retour. Bitte beachten Sie, dass die Deklaration bis am 26. April 2002 beim Amt in den USA eingereicht sein sollte.

Internet webserver
<http://www.frei-patent.com>
office-mail
@frei-patent.com

Winterthur office
Eidbergstrasse 64
8405 Winterthur
Tel. 052/232 43 66
Fax 052/232 33 95

Mit freundlichen Grüssen

FREI PATENTANWALTSBÜRO

Albert Meier

Postal check
PC 80-12725-3

Bank account
SBG/UBS Zürich
Bahnhofstrasse
Kto. 338214.01U

Member of the International Federation of Industrial Property Attorneys



P 165105

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

As the below named inventor(s), I/we declare that:

This declaration is directed to:

- ☐ The attached application, or
☒ Application No. PCT/CH01/00207, filed on April 2, 2001,
☐ as amended on _____ (if applicable);

I/we believe that I/we am/are the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought;

I/ we have reviewed and understand the contents of the above-identified application, including the claims, as amended by any amendment specifically referred to above;

I/we acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me/us to be material to patentability as defined in 37 CFR 1.56, including material information which became available between the filing date of the prior application and the National or PCT International filing date of the continuation-in-part application, if applicable; and

All statements made herein of my/own knowledge are true, all statements made herein on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF INVENTOR(S)

Inventor one: Arno Kleinhaeni Date: _____

Signature: _____ Citizen of: CH

Inventor two: Roman Mathiuet Date: X

Signature: X Citizen of: CH

Inventor three: _____ Date: _____

Signature: _____ Citizen of: _____

Inventor four: _____ Date: _____

Signature: _____ Citizen of: _____

☐ Additional inventors are being named on _____ additional form(s) attached hereto.

Burden Hour Statement: This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is used by the public to file (and the PTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This form is estimated to take 1 minute to complete. This time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Frei Patentanwaltsbüro

European Patent Attorneys
Conseils en Brevets Européens

Tel. 01/396 20 60
Fax 01/396 20 70

EINSCHREIBEN

Mailing address
Postfach 768
CH-8029 Zürich

Herrn
Roman Mathiuet
Kiesweid 17
8340 Hadlikon

Visiting address
Forchstrasse 420
CH-8702 Zollikon
(Zürich)

20. August 2002/yk

US-Patentanmeldung Nr. 10/018,060

"Security reversible key and locking system"

Ihr Zeichen: ---

Unser Zeichen: P1651 US

Sehr geehrter Herr Mathiuet

Als Anlage erhalten Sie folgendes Dokument:

- ☒ Deklaration
- ☒ Kopie der aktuellen Version der Anmeldung
- ☐ Übertragung

Bitte senden Sie uns die Deklaration datiert und signiert möglichst umgehend retour. Bitte beachten Sie, dass die Deklaration bis am 14. September 2002 beim Amt in den USA eingereicht sein sollte.

Mit freundlichen Grüßen

FREI PATENTANWALTSBÜRO

Albert Meier

Internet webserver
<http://www.frei-patent.com>
office-mail
@frei-patent.com

Winterthur office
Eidbergstrasse 64
8405 Winterthur
Tel. 052/232 43 66
Fax 052/232 33 95

Postal check
PC 80-12725-3

Bank account
SBG/UBS Zürich
Bahnhofstrasse
Kto. 338214.01U

Member of the International Federation of Industrial Property Attorneys



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

As the below named inventor(s), I/we declare that:

This declaration is directed to:

☐ The attached application, or☒ Application No. PCT/CH01/00207, filed on April 2, 2001,☐ as amended on _____ (if applicable);

I/we believe that I/we am/are the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought;

I/ we have reviewed and understand the contents of the above-identified application, including the claims, as amended by any amendment specifically referred to above;

I/we acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me/us to be material to patentability as defined in 37 CFR 1.56, including material information which became available between the filing date of the prior application and the National or PCT International filing date of the continuation-in-part application, if applicable; and

All statements made herein of my/own knowledge are true, all statements made herein on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF INVENTOR(S)Inventor one: Arno Kleinhaeni Date: _____Signature: _____ Citizen of: CHInventor two: Roman Mathiuet Date: _____ ☒Signature: _____ ☒ Citizen of: CH

Inventor three: _____ Date: _____

Signature: _____ Citizen of: _____

Inventor four: _____ Date: _____

Signature: _____ Citizen of: _____

☐ Additional inventors are being named on _____ additional form(s) attached hereto.

Burden Hour Statement: This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is used by the public to file (and the PTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This form is estimated to take 1 minute to complete. This time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

SECURITY REVERSIBLE KEY AND LOCKING SYSTEM

BACKGROUND OF THE INVENTION

[0001] The invention concerns a security reversible key with an assigned cylinder, a locking system with security reversible keys for locking systems, and a method for their manufacture. Such keys and locking systems are known, where the keys with a high degree of security and a correspondingly high number of possible coding permutations. The keys have at least three, and preferably at least four coding tumbler pin rows. The tumbler row pins are located on the flat sides of the key in order to make the best possible use of the available key surface, as well as the corresponding space requirement for the tumbler pin rows in the cylinder. Keys with additional security elements are also known, which once again require a certain amount of space.

[0002] From U.S. Patent No. 5,438,857, such a key is known, with an insertion blocking system as an additional security element. In the '857 key an additional control face is located on the key that, by means of an assigned control pin at the cylinder entrance, prevents the insertion of a wrong key. This control pin is longer than a coding pin and extends beyond the central bisecting plane of the key. The control face is arranged at the tip of the key and rising, and it correspondingly also extends beyond the central bisecting plane of the key and lifts the control pin and pushes the control pin out of the way. As a result of this, the control pin prevents the insertion of keys without a correct control face. The control faces can already be affixed to the key blank and with this enable a protection of the blank.

[0003] These known high-security keys and systems with high-security keys are also always limited by the space available for the coding and security functions on the key and in the cylinder. Their manufacture calls for a central production, which limits, renders more

difficult, and delays the world-wide universal application of such systems. Also, an optimum design for installations and applications of any kind is severely restricted by this.

SUMMARY OF THE INVENTION

[0004] It is an objective of the present invention to create a security reversible key with an assigned cylinder. More specifically, it is an objective of the invention to provide a locking system with security reversible keys and assigned cylinders, which can be utilized as a world-wide unique locking system, with higher permutation capacities for any kind of application, with enhanced security and copy protection as well as with new possibilities of being in a position to separate any kind of market area and application world-wide, and whereby, without any additional space requirement on keys and cylinders, a higher security and a greater number of permutations is achieved. A further objective of the present invention is a manufacturing method for a system of this kind, which can rapidly and

universally be brought into use and applied world-wide.

[0005] In accordance with the present invention, a security reversible key has an assigned cylinder, a locking system has security reversible keys with assigned cylinders, and a method is provided to manufacture such keys. in accordance with claim 19. With the new additional security element "blocking code", which comprises a coded blocking groove and an assigned pair of blocking tumbler pins, without any additional space requirement on the key and in the cylinder, i.e., with the existing coding positions on the key and the existing pin rows and positions in the cylinder, an additional insertion blocking system as well as a higher number of permutations and applications are achieved. With the division into areas on the key, whereby the first area with additional security elements defines an unequivocal segmentation

into independent market areas, a system is created that corresponds to the above named objective and which can be realized with the new, multi-step manufacturing process.

[0006] Especially with the new additional security element "blocking code", which comprises a coded blocking groove and an assigned pair of blocking tumbler pins, without any additional space requirement on the key and in the cylinder, i.e., with the existing coding positions on the key and the existing pin rows and positions in the cylinder, an additional insertion blocking system as well as a higher number of permutations and applications are achieved.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] These and further features of the invention are apparent with reference to the following description and drawings, wherein:

[0008] Fig. 1a shows coding rows with coding positions for two bore patterns on one key;

[0009] Fig. 1b shows on a key a division into areas, with a first area with additional security elements;

[0010] Fig. 1c shows a further example of a division into areas;

[0011] Fig. 1d shows a segmentation of market areas and distributor areas on a key;

[0012] Fig. 1e shows a connection between division into areas and segmentation of market areas;

[0013] Fig. 2 shows the principle of the blocking code with blocking groove and blocking tumbler pin pair;

[0014] Fig. 3 shows examples of coding steps and blocking steps;

[0015] Fig. 4 shows examples of different tumbler pin shapes;

[0016] Fig. 5 shows blocking groove shapes corresponding to Fig. 4;

- [0017] Fig. 6 shows coding shapes corresponding to Fig. 4;
- [0018] Fig. 7 shows a blocking groove extending over four positions with differing sectors;
- [0019] Fig. 8 shows, in a three-dimensional representation, a blocking groove with a blocking tumbler pin pair;
- [0020] Fig. 9 shows, in a three-dimensional representation, different examples of blocking grooves with coding positions (corresponding to the example of Fig. 14);
- [0021] Fig. 10 shows a security element "insertion block" by means of a control face and a control pin;
- [0022] Fig. 11 shows a security element "flat pin" for the flank control of codings;
- [0023] Fig. 12 shows a key with four rows of tumbler pins and with blocking pins in the cylinder;
- [0024] Fig. 13 shows examples of keys with five and with eight coding or tumbler pin rows;
- [0025] Fig. 14 shows a schematic locking function diagram with two bore patterns and two market areas;
- [0026] Fig. 15 shows a schematic locking function diagram with two positions and four market areas;
- [0027] Fig. 16 shows a schematic locking function diagram with two positions and one market area;
- [0028] Fig. 17 shows a schematic locking function diagram with one position each in two tumbler pin rows and with three market areas;
- [0029] Fig. 18 shows an organization diagram of a locking system with segmented market areas and applications; and,

[0030] Fig. 19 shows a schematic manufacturing diagram for keys of a locking system in accordance with the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0031] Fig. 1a, as an example, illustrates a safety turning-key S with four pin rows A1 to A4 and with 22 coding positions P_i , each one for a bore pattern left (L) and a bore pattern right (R). The coding row A2 on the key S here has the positions R1 to R5 for the bore pattern R and the positions L6 to L11 for the bore pattern L. On the keys, all positions of both bore patterns can be coded. For example, there are keys with bore pattern left, keys with bore pattern right and also keys with the two bore patterns R + L. In the assigned cylinder Z, however, for reasons of space for the pins, only every second position and, with this, only either a bore pattern R or a bore pattern L can be equipped with tumbler pins (in the same area). The first coding position $P_1 (= L_{11})$ on the tip of the key here corresponds to the

rearmost tumbler pin position P_1 in the cylinder with respect to the direction of insertion x of the key S.

[0032] Fig. 1b illustrates the locking system in accordance with the invention on a key S, whereby on the key at least two areas are defined with a first area G1, in which at least two additional security elements with a higher degree of difficulty to manufacture are foreseen, and with a second area G2, in which a simple basic coding Cod1 is foreseen. With the first area G1 an unequivocal segmentation into independent market areas $M_i = M_1, M_2$, etc. is defined.

[0033] Also illustrated here are additional security elements, which in the following are more accurately defined: a blocking code BC, a second coding Cod2, preferably with a narrow milling, an insertion blocking system by means of a control face and control pin

KF/KS and a flank control of Cod2 by means of a flat pin 23. The simple basic coding Cod1 is, for example, a coding by means of bores, which is relatively easily implementable anywhere decentralized.

[0034] Fig. 1c depicts a different division into areas, whereby the area G1 can be divided into several part areas G1.1, G1.2, etc. Depending on the application and on the desired system design, the area G1 can, for example, encompass a whole coding row A1. In doing so, also all security elements are affixed in this one coding row. In a different advantageous variant, for example, also parts of areas with positions at the very front of the key of two coding rows (A1, A2) can form the area G1, whereby both parts of areas G1.1, G1.2 can each respectively have a blocking code BC.

[0035] Fig. 1d illustrates the division into several independent market areas $M_i = M_1, M_2$, etc., as well as the possible further sub-division of each market area into parts of market areas M_{mi} , which are, for example, independent distributor areas or fields of application for

installations and objects, etc. The market areas M_i are defined with the area G1. The parts of areas M_{mi} can be defined with parts of the area G1 or also with parts of the area G2 or they can equally encompass parts of the areas G1 and G2.

[0036] Fig. 1e illustrates, for example, a connection between the areas G1, G2 on the key and the unequivocal separation in the market area M_i , parts of market areas M_{mi} as well as the further subdivisions for objects $M_{mi.i}$. This is further explained hereinafter with reference to Fig. 18.

[0037] Advantageously, the area G1 contains at least three security elements V_i . Particularly important and advantageous is the new additional security element "Blocking Code". In the case of the blocking code BC, as an additional coding and security function in

accordance with the invention explained in Fig. 2, the coding position P1 and its function on the key S and in the cylinder Z are maintained.

[0038] Fig. 2 schematically illustrates the method of operation of the blocking code BC in accordance with the invention on a key S and in an assigned cylinder Z. The directions in space are in the following designated with x, y, z, with x being the axis of the key and cylinder. The key has a blocking groove BN milled therein. The blocking groove BN runs parallel to the key axis x and extends at least up to the first coding position P1. In the assigned cylinder, correspondingly at least at the rearmost coding position P1, a pair of blocking tumbler pins is disposed. The blocking pins include a spring loaded blocking tumbler pin BZ and an extended blocking counter pin BG. The blocking groove has a coded blocking depth B1, B2, B3 and, in correspondence with this, the length lb of the pair of blocking tumbler pins (BZ + BG) is coded such that the length lb corresponds to the distance db of the blocking groove BN from the cylinder housing 10. In other words, the pair of blocking tumbler pins (or pair of blocking pins) fits in the blocking groove BN with little play. When inserting the key, the following sequence results (a - b - c): The blocking tumbler pin BZ is lifted at a beveled lead-in face 6 of the key up to the level of the blocking groove BN and with little play with the cylinder housing 10 passes through the blocking groove up to the corresponding coding position P1, whereby the blocking tumbler pin BZ is lowered into this first coding position with a certain coding step, here, e.g., C2. In this position P1 the pair of blocking tumbler pins BZ, BG operates as normal coding position with respect to turning of the cylinder, which in case of a correct coding has to release the shear line 9. If the blocking groove BN is not deep enough, such as when it has a wrong coding Bi, then the blocking counter pin BG impinges on the cylinder housing 10 and the further insertion of the key is blocked at the beveled lead-in face (if lb is larger than db, refer to Fig. 8a). The

blocking code therefore results in an additional security function, in that the complete insertion can be prevented with additional coding steps (B_i) of the blocking groove, whereby the coding function up until now at the position P1 is maintained. Over and above this, neither the key, (i.e., on the key positions) nor the cylinder requires additional space for the blocking code. In the cylinder simply an up until now the normal coding tumbler pin is replaced by the special blocking tumbler pin.

[0039] Fig. 3 illustrates possible blocking steps B_i with a depth t_b in comparison with the coding steps C_i with the coding depths t_c relative to the key surface. In the following examples, here coding steps C1 to C4 (e.g., steps of 0.35 mm) as well as three blocking steps B1, B2, B3 with blocking depths of, e.g., 1.05, 0.55 and 0 mm are utilized, whereby a blocking step B3 with a depth of 0 mm cannot exert a blocking function anymore. The blocking depths B_i can also correspond to the coding depths C_i , therefore, e.g., C1 to C4 and B1 to B4. In a further example, five coding steps C1 to C5 are represented in combination

with four blocking steps B1 to B4, e.g., with step distances of 0.3 mm of the C_i and of 0.4 mm of the B_i . In accordance with the combination rule for the blocking steps B_i with the coding steps C_i , the coding depth t_c of the coding steps C_i must not be smaller than the blocking depth t_b of the preceding blocking groove B_i . In this example, therefore the blocking step B3 can be combined with the subsequent coding steps C3, C2 or C1.

[0040] Figs. 4, 5 and 6 illustrate various possible tumbler pin shapes (Figs. 4a, b, c), assigned forms of the blocking grooves BN (Figs. 5a, b, c) as well as the coding shapes assigned to the tumbler pins (Figs. 6a, b, c). Fig. 4a illustrates a conventional conical tumbler pin shape 21, such as for a basic coding Cod1, which can be manufactured by means of simple bores (Fig. 6a). Fig. 4b depicts a narrow, cylindrical tumbler pin shape 22 with correspondingly narrow coding grooves (Fig. 6b), the manufacturing of which calls for a

difficult to copy, elaborate milling process and which, for example, can be utilized as a second coding Cod2. Fig. 4c illustrates a flat pin 23, which, e.g., can be utilized for the flank control of a narrow milled coding (Fig. 6b), as will be explained in more detail later on. Further tumbler pin shapes are possible and known, which in principle are a combination of cylindrical and conical sections. The blocking groove shapes and the coding shapes can be implemented differently and as a result make any copying more difficult and also have the effect of additionally obscuring the coding shapes.

[0041] The Figs. 7a, b, c illustrate an example of a blocking groove, which extends over the four most forward coding positions $P_i = L11, R5, L10$ and $R4$ of two bore patterns R, L and which correspondingly have several differently coded sectors BN1 to BN4. In doing so, as a rule attention must be paid, that the depth t_b of the blocking grooves remains the same from one position to the next position or else becomes smaller (i.e., cannot become bigger) and that equally the width b_b of the blocking grooves remains the same from one position to the next one or else becomes smaller. This in conjunction with three blocking steps B1 to B3 and with two blocking groove widths b_{b1} and b_{b2} results in the illustrated blocking steps B_i, b_{bi} of the four blocking groove sectors BN1 to BN4.

[0042] Fig. 8 illustrates the function of the blocking code in a three-dimensional depiction and Fig. 9 blocking groove shapes and the adjacent coding indentations, which correspond to the example of Fig. 14. In Figs. 8a, b a key S1a is illustrated, with a blocking groove, which has a blocking step B2 and with adjacent coding positions L11 and R5, which have the codings C1 and C2 (corresponding to the key S1a of Fig. 14).

[0043] Fig. 8a illustrates a pair of blocking tumbler pins BZ, BG with blocking code B1, the length l_b of which is greater than the distance d_b of the blocking groove from the cylinder housing 10. With this, the complete insertion of the key S1a into this cylinder is blocked. Fig.

8b in contrast illustrates a pair of blocking tumbler pins BZ, BG with a blocking code B2, which corresponds to the blocking code B2 of the blocking groove BN and which, therefore, can be completely inserted. This in the schematic diagram of Fig. 14 corresponds to the key S1a, which opens the cylinder Z1 (with coding C1 at the position R5).

[0044] The Figs. 9a to 9d illustrate the keys S1, S2, S3 and S1a, with differently coded blocking grooves and positions L11 and R5. This also corresponds to the schematic locking function diagram of Fig. 14, which indicates, which key - cylinder combinations open and which ones block.

[0045] Fig. 10 as possible additional security element illustrates an as such known insertion blocking system by means of a control face KF at the tip of the key and an assigned control pin KS in the cylinder. This control face KF extends beyond the central bisecting plane 5 of the key, the same as the control pin KS, which impinges on the rising control face KF and has to be pushed out of the way by it in order for the key to be able to be inserted. A

key without the right control face, resp., with only normal lead-in faces 6, with its tip encounters this control pin KS, so that the latter prevents the insertion of the key. This is a completely different arrangement and action than according to the blocking code in accordance with the invention, which does not require any special control faces, but works rather more with any existing key lead-in face 6. Advantageously, however, the new blocking code with the blocking tumbler pins BZ can be combined with this known insertion block by means of control faces KF and control pin KS and in particular even be assigned in the same tumbler pin row (e.g., A2), whereby the control pin KS is positioned anywhere in front of the pair of blocking tumbler pins BZ, BG in the cylinder.

[0046] A further important additional security element, which can also be assigned in the same tumbler pin row, is illustrated in Figs. 11a, 11b. These illustrate a flank control at a

narrow coding milling Cod2, which is implemented by a flat tumbler pin 23. The flat tumbler pin 23 (refer to, e.g., Fig. 4c) has a diameter d_2 , which is greater than the width d_1 of the coding milling, so that the flat tumbler pin lies on the key surface 7, as is depicted in Fig. 11a. In contrast, in the case of a basic coding Cod1, e.g., in accordance with Fig. 6a, with necessarily wide bores d_3 the flat tumbler pin 23 will sink into these indentations in accordance with Fig. 11b, whereby the shear line 9 of the cylinder is blocked. With this, e.g., a simple forged bore instead of the authorized, much more elaborate narrow coding milling Cod2 can be detected and the functioning of a key forged in this manner be prevented.

[0047] Advantageously therefore in a tight space and in a single tumbler pin row the following very effective security elements can be combined: in addition to the blocking code BC in accordance with the invention, a second coding Cod2 with a narrow milling, an insertion control by means of control pin KS and control face KF as well as a flank control of the narrow coding Cod2 by means of a flat tumbler pin 23.

[0048] Fig. 12 illustrates a cross section through a safety turning-key with four rows of tumbler pins A1 to A4 in a cylinder in accordance with the example of Fig. 1. The row A1 here is implemented with a narrow coding milling Cod2 and with a pair of blocking tumbler pins BZ, BG. The rows A3 and A4 (and optionally also the row A2) here are implemented with a simpler basic coding Cod1. Important is to exploit the given key surface and the space inside the cylinder in the best possible way for coding positions and security elements. To achieve this, of necessity (at least two) rows of tumbler pins also have to be located on the flat sides of the key.

[0049] In the case of somewhat bigger keys, it is also possible to foresee more than four rows of tumbler pins.

[0050] Fig. 13a for this purpose illustrates an example with five rows of tumbler pins A1 to A5 and Fig. 13b an example with eight rows of tumbler pins A1 to A8, which, however, can only be equipped with tumbler pins in the cylinder to such an extent as space is available. Thanks to the utilization of narrow codings, however, it is also possible to code all eight rows on the key here. This results in a great number of possible permutations as well as in further security reserves. In principle, here too at the beginning of every row of tumbler pins A_i , a blocking coding can be provided.

[0051] In the Figs. 14 to 17, schematic locking function diagrams with different combinations of blocking codes B_i and codings C_i of the adjacent positions P_i are illustrated. In the left-hand column, the codings B_i , C_i of the keys S_i are indicated and in the row on top the codings of the cylinders Z_i . The keys can have the bore patterns R or L, or R + L (both), while the cylinders can only contain one bore pattern R or L. The schematic diagram indicates with an "X", whether a combination key / cylinder fits, i.e., whether the key opens the corresponding cylinder. All other combinations block. The Figs. 14 to 17 illustrate how, with few blocking codings B_i and adjacent position codings C_i , different market areas M_i can be unequivocally differentiated between, and how within a market area several derivations, i.e., hierarchic differentiations, of keys can be implemented within an installation.

[0052] The schematic diagram of Fig. 14 (which corresponds to the Figs. 8 and 9) illustrates codings C_i with two bore patterns and with two positions

[0053] $P1=L11$ and $P2=R5$ with 5 equipping alternatives with blocking steps $B_i = B1, B2, B3$ of the blocking grooves and coding steps $C_i = C1$ and $C2$.

[0054] Defined with this are two independent market areas $M1, M2$ With three, resp., two derivations. The key $S3$, e.g., opens the cylinders $Z1$ and $Z3$.

[0055] Fig. 15 illustrates only one bore pattern L with blocking code over two positions $P1 = L11$ and $P2 = L10$ with blocking steps B1, B2, B3 and with coding steps C1, C2.

[0056] Defined with this are four independent market areas M1 to M4, each with three derivations.

[0057] For example, the key S11abc opens the cylinders Z11a, Z11b, Z11c.

[0058] Fig. 16 illustrates a bore pattern L with two positions $P1 = L11$ and $P2 = L10$ with blocking code B1, B2, B3 and coding steps $L11 = C1$ and $L10 = C1$, whereby with the blocking steps within a market area five derivations are created. For example, the key S11abcde opens the five cylinders Z11a to Z11e and the key S11a only opens the cylinder Z11a.

[0059] Fig. 17 illustrates an example with only one position P1 each, however, in two rows of tumbler pins A1, A2. Both positions P1 are coded with C1, while with the blocking steps B1, B2, B3 of the blocking grooves three independent market areas M1, M2 and M3 are defined.

[0060] The key S1 only opens the cylinder Z1, S2 only opens Z2, and S3 only opens Z3.

[0061] Fig. 18 illustrates an organization of the locking system in accordance with the invention with security reversible keys in a hierarchic schematic diagram. The system owner SS (e.g., a manufacturing company) represents the highest hierarchic level, which defines and authorizes the market areas $M_i = M1, M2$, etc., whereby a market area may be a country or a general distributor. In the market areas, further parts of areas M_{mi} are defined and separated and may be, for example, for different distributors or installations within this area. A further level $MM_{i,i}$ can define individual objects. This is defined by the codings of the areas G1 and G2.

[0062] Fig. 19 schematically illustrates a manufacturing method for keys of a system in accordance with the invention with manufacturing steps H, areas G on the key and with the manufactured variables Vi in the areas G. On principle the manufacturing H with reducing degree of difficulty HS takes place on lower levels, respectively, decentralized.

[0063] The variables Vi and security elements manufactured in the various areas Gi and in the corresponding manufacturing steps Hi, for example, are also indicated in the table.

[0064] With the manufacturing of keys and cylinders of a locking system with at least two areas G1 G2 on the keys, first the first area on the keys is manufactured (controlled and authorized) at a central place of manufacture H1 and the coding Cod1 of the keys of the second area G2 and the equipping of the cylinders with corresponding pins can subsequently take place at a local representative: H2.

[0065] The manufacturing can take place in at least two steps in different places, whereby ~~first variables with a higher degree of difficulty HS of the area G1 are manufactured in a~~ central location and subsequently variables with a lower degree of difficulty of the area G2 are manufactured decentralized or locally.

[0066] The manufacturing of the keys can also take place in three steps, whereby first the first area G1 with variables Vi of the highest degree of difficulty is manufactured centrally : H1; thereupon a further area G1/2 with variables with a lower degree of difficulty is manufactured regionally : H1/2 and finally the coding G2 with the lowest degree of difficulty of the area G2 is manufactured locally at the place of use H2.

[0067] In a further development of the system, the manufacturing of the area G1 can also take place decentralized. To implement this, manufacturing programs and the authorization "aut" can be controlled and checked from the central location SS (system owner).

[0068] With the system in accordance with the invention and the manufacturing methods a universal differentiation of market areas and parts of market areas as well as a rapid local manufacturing are made possible.

[0069] Within the framework of this description, the following designations are used:

[0070]	x, y, z	Directions in space
[0071]	x	Key axis
[0072]	S, Si	Key
[0073]	Z, Zi	Cylinder
[0074]	Pi	Coding positions
[0075]	R, L	Right-hand -, left-hand bore pattern
[0076]	Ri, Li	Right-hand -, left-hand coding positions
[0077]	Ai	Coding rows, pin rows
[0078]	Bi	Coded blocking steps
[0079]	Ci	Coding steps
[0080]	BC	Blocking code
[0081]	BN	Blocking groove
[0082]	BZ	Blocking tumbler pin
[0083]	BG	Blocking counter pin
[0084]	BZ + BG	Pair of blocking tumbler pins, pair of blocking pins
[0085]	1b	Length of BZ + BG
[0086]	db	Distance from BN to $\frac{1}{10}$
[0087]	tb	Depth of BN
[0088]	bb	Width of BN
[0089]	tc	Depth of the coding steps Ci

[0090]	d1, d2, d3	Diameters
[0091]	Cod1	Basic coding
[0092]	Cod2	Second (different) coding
[0093]	KF	Control face
[0094]	KS	Control pin
[0095]	Mi	Market areas
[0096]	MMi	Parts of market areas
[0097]	SS	System owner
[0098]	aut	Authorization
[0099]	H1, H2	Manufacturing steps
[00100]	HS	Degree of manufacturing difficulty
[00101]	G1, G2	Areas on S
[00102]	Vi	Variables, security elements
[00103]	5	Central bisecting plane of S
[00104]	6	Beveled tip of S, lead-in face of S
[00105]	8	Surface of S
[00106]	9	Shear line in Z
[00107]	10	Cylinder housing
[00108]	11, 12	Supporting surfaces at tumbler pins
[00109]	15	Beveled face at tumbler pins
[00110]	21 - 23	Various shapes of tumbler pins
[00111]	23	Flat pin

IN THE CLAIMS:

Please amend the claims as follows:

1. (amended) A security reversible-key with at least three coding/tumbler pin rows (A1, A2, A3) located on the flat sides of the key (S), with an assigned cylinder (Z) with pin rows of pairs of tumbler pins, said tumbler pin pairs consisting of tumbler pins and counter pins at the positions of the tumbler pin rows of a given bore pattern, wherein:
the key has a blocking groove BN that runs parallel to an axis (x) of the key from a tip of the key to at least a first position (P1) of a tumbler pin row on the key,
the blocking groove has a coded blocking depth (B1, B2, B3) that, in the assigned cylinder at least at a rearmost coding position (P1), a pair of tumbler pins corresponding to the blocking groove (BN) with a blocking tumbler pin (BZ) and an extended blocking counter pin (BG) are received,
so that the blocking counter pin impinges on the cylinder housing (10) if the blocking groove is not deep enough and complete insertion of a key with an insufficiently deep blocking groove is blocked by the pair of blocking tumbler pins and whereby the blocking tumbler pin (BZ) together with the blocking counter pin (BG), following insertion of the key at the rearmost coding position (P1), is also utilized as a coding tumbler pin with coding steps (C1, C2, C3, C4) for turning of the cylinder.
2. (amended) The key in accordance with claim 1, wherein at least four rows of tumbler pins (A1 - A4) are provided.
3. (amended) The key in accordance with claim 1, wherein at least two different codings (Cod1, Cod2) are provided.
4. (amended) The key in accordance with claim 1, wherein coding positions (Pi) from two different bore patterns (R, L) are provided.
5. (amended) The key in accordance with claim 1, wherein the blocking groove, which runs to at least the first and rearmost coding positions (P1, P2) at the very front of a coding row (A2) and by blocking tumbler pins BZ1, BZ2 and blocking counter pins BG1,

BG2 corresponding to the coding positions, with coded step depths of these at least two positions at the very front.

6. (amended) The key in accordance with claim 5, wherein the blocking groove has at least two differently shaped sectors BN1, BN2.

7. (amended) The key in accordance with claim 1, wherein the blocking groove extends over more than one coding position and whereby the depth (tb) of the blocking groove is constant or decreases from one coding position (P1) to the next coding position (P2).

8. (amended) The key in accordance with claim 1, wherein the blocking groove extends over more than one coding position and whereby the width (bb) of the blocking groove remains constant or decreases from one position (P1) to the next position (P2).

9. (amended) The key in accordance with claim 1, wherein at more than one row of tumbler pins (A1, A2), respectively, one blocking groove each with assigned pairs of blocking tumbler pins is provided.

10. (amended) The key in accordance with claim 1, wherein, as an additional security element, a rising control face KF is disposed at the tip of the key, said control face KF pushes an assigned control pin KS out of the way, whereby the control pin KS prevents insertion of a key without a control face KF.

11. (amended) The key in accordance with claim 10, wherein the control pin KS is a flat pin (23), which also carries out a flank control at a narrow coding milling (Cod2).

12. (amended) The key in accordance with claim 1, wherein, in a row of tumbler pins (A2), the following security elements are located: blocking code (BC), second coding (Cod2), insertion blocking system by means of control face (KF) and control pin (KS) as well as flank control by means of a flat pin (23).

13. (amended) A locking system with security reversible keys for locking systems with at least three coding/tumbler pin rows (A1, A2, A3), which are also located on the flat sides of the keys (S), with assigned cylinders (Z) with pin rows of pairs of tumbler pins, consisting of tumbler pins and counter pins at the positions of a given bore pattern and with at least two additional safety elements, wherein at least two areas on the keys are defined such that, in a first area (G1), at least two additional security elements with a higher degree of manufacturing difficulty are provided and, in the second area (G2), a more simple basic coding (Cod1) is provided, and wherein, with the first area (G1) an unequivocal segmentation into independent market areas (M1, M2, ...) is defined whereby the first area (G1) has, as an additional security element, a blocking code (BC), the keys have a blocking groove (BN) that runs parallel to an axis of the key (x) from a tip of the key to at least a first position (P1) of a tumbler pin row on the key, the blocking groove has a coded blocking depth (B1, B2, B3), in the assigned cylinder at least at the rearmost coding position (P1), a pair of tumbler pins with a blocking tumbler pin (BZ) and an extended blocking counter pin (BG) corresponding to the blocking groove (BN) are provided such that the blocking counter pin BG impinges on the cylinder housing (10) if the blocking groove is not deep enough to thereby block complete insertion of a key with an insufficiently deep blocking groove by the pair of blocking tumbler pins, and whereby the blocking tumbler pin (BZ) with the blocking counter pin (BG) after insertion of the key at the rearmost coding position (P1) is also utilized as a coding tumbler pin with coding steps (C1, C2, C3, C4) for turning of the cylinder.

14. (amended) The locking system in accordance with claim 13, wherein, as security elements in the first area (G1), a second coding (Cod2), an insertion blocking comprising control faces (KF) on the key and assigned control pin (KS) in the cylinder, and a flank control comprising a flat tumbler pin (23) and a blocking code (BC) are provided.

15. (amended) The locking system in accordance with claim 13, wherein, the keys include areas having different bore patterns (R, L).

16. (amended) The locking system in accordance with claim 13, wherein at least three security elements are provided in the first area (G1).

17. (amended) The locking system in accordance with claim 13, wherein, as security elements, a second coding (Cod2) with a narrow milling is provided.

18. (amended) The locking system in accordance with claim 13, wherein all security elements of the first area (G1) are affixed in one coding row (A2).

19. (amended) A method for manufacturing keys and cylinders of a locking system with at least two areas (G1, G2) on the keys (S) in accordance with claim 13, wherein first the first area (G1) on the keys is manufactured in a central place of manufacture (H1), and that the coding (Cod1) of the keys of the second area G2 and the equipping of the cylinders with corresponding pins is subsequently manufactured at a remote location by local representative (H2).

20. (amended) The method in accordance with claim 19, wherein manufacturing takes place in at least two steps at different locations, whereby first variables with a higher degree of difficulty (HS) of the first area (G1) are manufactured at a central location and subsequently variables with a lower degree of difficulty of the second area (G2) are manufactured in a second decentralized location.

21. (amended) The method in accordance with claim 19, wherein manufacturing of the keys takes place in at least three steps, whereby first the first area (G1) with variables of the highest degree of difficulty is manufactured centrally (H1), thereupon a further area (G1/2) with variables with a lower degree of difficulty is manufactured regionally (H1/2) and finally the coding with the lowest degree of difficulty of the second area (G2) is manufactured locally at the place of application (H2).

22. (amended) The method in accordance with claim 19, wherein the manufacturing of the first area (G1) is also able to take place decentralized, whereby manufacturing programs and authorization for a desired operation are controlled and checked from a central location.

IN THE ABSTRACT:

Please replace the original abstract with the following:

ABSTRACT OF THE DISCLOSURE

The security reversible key with an assigned cylinder (Z) has a blocking groove (BN) with a coded blocking depth (B1, B2, B3), which runs parallel to the axis of the key (x) from the tip of the key to at least the first position (P1) of a row of tumbler pins (A2) on the key. In the assigned cylinder, at least at the rearmost coding position (P1), a pair of tumbler pins corresponding to the blocking groove (BN) with a blocking tumbler pin (BZ) and an extended blocking counter pin (BG) are provided. The blocking counter pin (BG) impinges on the cylinder housing (10) if the blocking groove is insufficiently deep and, with this, complete insertion of a key with an insufficiently deep blocking groove is blocked by the pair of blocking tumbler pins. Simultaneously, the blocking tumbler pin (BZ) with the counter pin (BG) at the position (P1) also serves as coding tumbler pin. In the case of the locking system with security reversible keys for locking installations at least two areas are defined. In a first area (G1) ~~several additional security elements and a blocking code function are provided~~ while, in the second area (G2), a more simple basic coding are foreseen. With the first area (G1), an unequivocal segmentation into independent market areas (M1, M2, M3) is defined and, with this, a world-wide unique locking system with enhanced security and applicability is created.